

**hp** scanjet 8290 digital flatbed scanner



datasheet

Revolutionize the workplace with the HP Scanjet 8290. Get fast, unattended multi-page scanning—up to 25 pages per minute and two-sided scanning with the included automatic document feeder. And with the industry-leading document management software, and ISIS and TWAIN drivers, it will enable you to keep your workplace operating efficiently and clutter-free. Get professional-quality scans—with 4800-dpi optical resolution and 48-bit color. And connecting to your computer is easy with Hi-Speed USB (compatible with USB 2.0 specifications), or SCSI connectivity with the included SCSI kit and module. You can even scan up to legal-size documents.

# fast multi-page scanning

 unattended multi-page scanning up to 25 pages per minute plus two-sided scanning with included automatic document feeder

# advanced document management

 industry-leading document management software makes document management a breeze

# professional quality results

- high resolution scanning at 4800-dpi optical resolution and 48-bit color for creating impressive business presentations and more
- capture scans from 35 mm negatives and slides using the transparent materials adapter built into the scanner lid

# easy connectivity

- compatible with PC's and Macintosh® computers —all setup materials included
- easy connection to your PC with the included industry standard SCSI Kit for PC or Mac® and SCSI module, or Hi-Speed USB (compatible with USB 2.0 specifications), plus compatible with Microsoft® NT® 4.0 or Mac

# larger scanning surface

• large scanning surface enables you to scan up to legal-size documents

# fast

- 6 one-touch buttons—launch tasks such as save, email and copy scans without using your keyboard
- copier-like performance for fast, high-quality scans

# hp scanjet 8290 digital flatbed scanner

# technical specifications

Scanner Type flatbed with ADF

### Scan Input Modes

HP photo & imaging software; front panel buttons, scan document, scan picture, copy, e-mail, edit text or file HP PrecisionScan Pro (with NT® 4.0); user application via TWAIN or ISIS drivers; TMA; and up to 25 ppm ADF

Image Technology

charge coupled device (CCD)

#### **Auto Document Feeder**

### Auto Document Feeder Speed

up to 25 ppm

#### Scan Resolution

optical: 4800 x 4800 dpi

opicus. 4000 x 4600 dpi enhanced: 4800 x 4800 dpi enhanced: up to 999, 999 dpi The maximum dpi at which you can scan is limited by available computer memory disk space and other system factors.

### Color Bit Depth

48-bit

## Grayscale Levels

256

# Preview Speed

4 secs\*

# Task Speed

A x 6 inch color photo into MS Word: less than 29 secs\*
OCR full page of text into MS Word: less than 47 secs\*
4 x 6 inch photo into e-mail: less than 31 secs\*
\* preview and task speeds are measurements using a 1.7 GHz PC with 256 MB RAM and Microsoft® Windows® 2000 Professional and a Hi-speed USB 2.0 (compatible with USB 2.0 specifications) interface

Scan Document To button (with rocker switch for destinations on 16-character LCD), Scan Picture button, Edit Text (OCR) button, File Document button, E-mail button, Copy button (with number of copies and black and white versus color), Power Save button, Button settings, Cancel button

Image Scaling or Enlargement Range

# 10 to 2000% in 1% increments

Maximum Document Scan Size

### $8.5 \times 14 \text{ in}$ Media Types

paper (plain, inkjet, photo), photos, envelopes, labels, business cards, 3D objects, negatives and 35 mm slides with Transparent Materials Adapter (TMA)

# External I/O Ports

1 USB, SCSI

### Connectivity

Hi-Speed USB (compatible with USB 2.0 specifications), SCSI connectivity (SCSI kit and module included

# ordering information

#### hp scanjet 8290 C9933A

hp scanjet 8290; hp scanjet transparent materials adapter (TMA) for scanning 35mm negatives and slides; up to 25 ppm automatic document feeder (ADF); USB cable; external power adapter; SCSI interface kit (SCSI card, cable and software); SCSI module with NT 4.0 compatibility; user's manual; ISIS & TWAIN drivers; CD-ROMs with software for Microsoft Windows and Macintosh: hp photo & imaging software with share-to-web software and hp memories disc creator, hp scanjet copy utility, suite of electronic tools: NewSoft Presto! BizCard Reader; IRIS Readiris Pro; Adobe® PhotoShop Elements; ScanSoft PaperPort Deluxe; ScanSoft OmniForm; Kofax VRS; Pixel Translations ISIS drivers; QuickScan  $Pro^{TM}$  (trial edition); NSI OneStep; alternate TWAIN driver; additional Microsoft Windows software: Adobe Acrobat® Reader™: NT 4.0: PrecisionScan Pro CD

# for more information

Visit us on the world wide web at www.hp.com.

#### Twain Version, Scanner

Twain driver included: version 1.9 for hp photo & imaging software, version 1.8 for NT 4.0 PrecisionScan Pro

Compatible Operating Systems
Microsoft Windows 98, 2000, Me, XP Home and Professional Editions, NT 4.0; Mac® OS 9.1 or higher, Mac OS X 10.1.5 or 10.2 or higher (some 3rd party software not compatible with Mac)

# Minimum System Requirements

Please note in-box software may require higher minimum system requirements. For Microsoft Windows and Macintosh®: CD-ROM drive; 64 MB RAM; 175 MB hard disk space plus 50 MB for full-color scanning for Pc; 240 MB available disk space for Macintosh; hp memories disc creator software requires CD writer and 700 MB additional hard disk space; SVGA monitor (800 x 600, 16-bit color); USB port For Microsoft Windows: PC with Pentium® II processor, Celeron or compatible; Microsoft Windows 98, 2000; Me; XP Professional or XP Home Edition, Microsoft Windows Internet Explorer 5.0

Internet Explorer 5.0
For Macinhosh: 233 MHz PowerPC processor (includes iMac); Mac OS 9.1 or higher; or OS X 10.1.5 or higher, or 10.2 or higher
Minimum system requirements for NT 4.0: PrecisionScan Pro: SCSI module on scanner;
SCSI compatible connection on PC; PC Pentium II, Celeron or compatible for Microsoft
NT 4.0, 32 MB RAM, 50 MB hard disk space for full-color scanning, CD-ROM drive,
SVGA monitor (800 x 600)

### Operating Environment

operating temperature range: 50 to 95° F (10 to 35° C) storage temperature: 40 to 158° F (40 to 70° C) recommended operating humidity: 15 to 85% RH

Dimensions (W x D x H) 22.6 x 15.7 x 7.7 in (574 x 399 x 196 mm)

Weight 19 lb (8.6 kg)

# Power Supply

Power Features: Universal AC adapter; 100 to 240 VAC, 50/60 Hz input; 32 VDC, 2.0 amp output

### **Power Consumption**

80 watts

one year-limited warranty backed by HP Customer Care, service and support

Electromagnetic Compatibility

EU (CE certification of conformity), North America (FCC), Australia (SMA), New Zealand (SMA), Russia (GOST), Korea (MIC), Taiwan (BSMI)

EU (IEC 60950 third edition compliant; third party Safety Certification), North America (nationally-recognized testing laboratories), Poland (PCBC), and Russia GOST

## Multiple File Formats

BMP, TIFF, GIF, PDF, HTML, JPEG, FlashPix (FPX), TIFF compressed, PCX, RTF, TXT, PNG

Windows® and Microsoft Windows® are U.S. registered trademarks of Microsoft Corp., Mac and Macintosh are registered trademarks of Apple Computer, Inc., Pentium is a U.S. registered trademark of Intel Corporation. ENERGY STAR is a U.S. registered service mark of the U.S. EPA. As an ENERGY STAR partner, Hewlett-Packard has determined that this product meets the guidelines for energy efficiency. All other brand and product names are trademarks or registered trademarks of their respective companies. Technical Information in this document is subject to change without notice

